







## Grupo TERMOCOL Hot Melt Adhesives - Hotmelt

| Ref. | Description                                       | Applications  | Speed meters/min | Temp. °C Roller  | Thermal resistance °C | Container format   |
|------|---|---|------------------|------------------|-----------------------|--|
| 1T   | Termocol 1T Invisible thermofuse                  | Invisible thermofuse, automatic gluing and Machining Center (BAZ). No Charges. Invisible glue line.               | 6-30             | 180-200 °C       | 95 °C                 | <br>Bag 25 Kg    Cube 10 Kg   |
| 2N   | Natural Universal Hot Fuse                        | Universal hot melt, automatic gluing of straight edges. Pre-glued thick edges.                                    | 6-30             | 180-200 °C       | 95 °C                 | <br>Bag 25 Kg    Cube 10 Kg   |
| 2B   | White universal thermofuse                        | Universal hot melt, automatic gluing of straight edges. Pre-glued thick edges.                                    | 6-30             | 180-200 °C       | 95 °C                 | <br>Bag 25 Kg    Cube 10 Kg  |
| 3N   | Termocol 3N hot melt High Fusion Natural          | Universal hot melt, automatic gluing of straight edges.   | 8-60             | 210 °C           | 102 °C                | <br>Bag 25 Kg   |
| 3B   | Termocol 3B hot melt High White Fusion            | Universal hot melt, automatic gluing of straight edges.   | 8-60             | 210 °C           | 102 °C                |  |
| 4N   | Termocol 4N hot melt Manual and Natural Pregluing | Low melting, low temperature application. Edging in a manual machine and pre-gluing of thin edges.                | 5-15             | 150 °C           | 91 °C                 | <br>Bag 25 Kg   |
| 5N   | Termocol 5N hot melt Cartridge HolzHer Natural    | Universal hot melt, automatic gluing of straight edges. Cartridge for HolzHer machine. Natural color gluing line. | 6-30             | Fuser 190-210    | 102 °C                | <br>Box 50 cartridges/15 Kg > 5 N<br>Box 50 cartridges/15 Kg > 5 B<br>Box 50 cartridges/11 Kg > 5 T |
| 5B   | Termocol 5B hot melt Cartridge HolzHer White      | Universal hot melt, automatic gluing of straight edges. Cartridge for HolzHer machine. White gluing line.         | 6-30             | Fuser 190-210    | 102 °C                |  |
| 5T   | Termocol 5T Invisible Hot Melt                    | Universal hot melt, automatic gluing of straight edges. Invisible glue line.                                      | 6-30             | Fuser 170-180 °C | 102 °C                |  |



## Grupo PURCOL-PR Polyurethane Adhesives

| Ref.                | Description                       | Applications   | Speed meters/min | Temp. °C Roller | viscosity mPas  | Container format  |
|---------------------|-----------------------------------|--|------------------|-----------------|-----------------|---|
| <b>5N PUR</b>       | <b>PURCOL PR 5N PUR Natural</b>   | Hot melt polyurethane NATURAL COLOR. Gluing of straight edges in a machine prepared with a gluing group for PUR adhesive.                        | 10-60            | 120-150 °C      | 120.000 ±20.000 | 2 kg cartridge Box of 9 cartridges<br>     |
| <b>5B PUR</b>       | <b>PURCOL PR 5B PUR White</b>     | Hot melt polyurethane WHITE COLOR. Automatic gluing of straight edges in a machine equipped with a gluing group for PUR adhesive.                | 10-60            | 120-150 °C      | 120.000 ±20.000 | 2 kg cartridge Box of 9 cartridges<br>     |
| <b>5T PUR</b>       | <b>PURCOL PR 5T PUR Invisible</b> | Hot melt polyurethane INVISIBLE, without charges. Automatic gluing of straight edges in a machine equipped with a gluing group for PUR adhesive. | 10-60            | 120-150 °C      | 120.000 ±20.000 | 1,8 kg cartridge Box of 9 cartridges<br> |
| <b>CLEAN 1,6-CA</b> | <b>LA Cleaner</b>                 | Cleaning product in cartridge for PUR adhesive gluing unit. Yellow color.  | -                | 120-160 °C      | 1.500           | 1,6 kg cartridge Box of 9 cartridges<br> |






## Grupo VINICOL Polyvinyl acetate dispersion based adhesive VINYL ADHESIVE

| Ref. | Description                                    | Applications  | Drying/Setting Time | Container format   |
|------|--|---|---------------------|--|
| 50U  | <b>High resistance Universal White Glue D2</b> | Type D2. Universal gluing, all kinds of wood, boards etc. Assembly and assembly work. Stratified and sheets on chipboard, MDF or plywood. Transparent glue joint.   | Normal              | <p>Cube 25 Kg    Cube 5 Kg    Feeding bottle 0,75 Kg</p> |
| 51R  | <b>Moisture resistant Fast White Glue D3</b>   | Type D3. Fast white glue, resistant to moisture. Ideal for gluing parquet floors, slats, manufacturing doors and windows, kitchen countertops, carpentry in general. Laminates and natural veneers on MDF boards. Transparent glue joint. | Average speed       | <p>Cube 25 Kg    Cube 5 Kg    Feeding bottle 0,75 Kg</p> |
| 52R  | <b>Quick assembly glue yellow D2</b>           | Type D2. Indicated for ultra-fast gluing of chairs, tables and all kinds of furniture structures, cold, hot or high frequency. Allows for gluing hard woods. Yellow glue joint.   | Average speed       | <p>Cube 25 Kg    Cube 5 Kg    Feeding bottle 0,75 Kg</p> |
| 53SR | <b>Super fast express assembly white glue</b>  | Type D2 Express. High performance super fast white glue. For furniture assembly with short pressing time. Gluing of chipboard, MDF and wood. Transparent glue joint.  | Super fast          | <p>Cube 25 Kg    Cube 5 Kg    Feeding bottle 0,75 Kg</p> |




## Grupo PURCOL-L Polyurethane Adhesive

| Ref. | Description   | Applications  | Drying/Setting Time | Container format                                   |
|------|---|---|---------------------|--|
| 90   | <b>One-component liquid PUR universal adhesive D4</b> | Type D4. PUR Universal, reticulates with humidity. For super strong, high strength bonds at the temp. and to the water. Gluing of various materials: wood, cement, metal, plastic, melamine, mouldings, etc. Indicated for work abroad. | Average speed       | <p>Feeding bottle 0,75 Kg    Box of 12 bottles</p> |





## Grupo ACRILIM Cleaning Product/Disinfectant

| Ref.   | Description                                  | Applications  | Properties                        | Container format  |
|--------|--|---|-----------------------------------|---|
| AC1-1A | Non-aggressive cleaning liquid. 520cc spray. | Cleaning of materials non-porous such as melamine, lacquered, plastic materials, edges of all kinds, etc. suitable for cleaning the remains of adhesive embedded in the edging machine. | Disinfectant<br>Total evaporation |  Spray 520 g. Box 6 u.               |
| AC3-1G | Non-aggressive cleaning liquid. 5l bottle.   | Non-aggressive cleaning liquid. 5l bottle.  | Disinfectant<br>Total evaporation |  5 L bottle.                         |
| AC2-1G | Non-aggressive cleaning liquid. 25l bottle.  | Cleaning of materials non-porous such as melamine, lacquered, plastic materials, edges of all kinds, etc. suitable for cleaning the remains of adhesive embedded in the edging machine. | Disinfectant<br>Total evaporation |  25 L bottle.<br>36 pallet bottles. |

### HAND APPLICATION



### MACHINE APPLICATION

